



(10) International Publication Number  
**WO 2005/062385 A1**

**PCT**

(43) International Publication Date  
7 July 2005 (07.07.2005)

- (51) International Patent Classification?: **H01L 29/739, 29/78, 29/10**
- (21) International Application Number: **PCT/JP2004/018432**
- (22) International Filing Date: **3 December 2004 (03.12.2004)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
- |             |                               |    |
|-------------|-------------------------------|----|
| 2003-427768 | 24 December 2003 (24.12.2003) | JP |
| 2004-092975 | 26 March 2004 (26.03.2004)    | JP |
- (71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA (JP/JP); 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HOTTA, Koji**


[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP). KAWAJI, Sachiko [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi, 4801192 (JP). SUGIYAMA, Takahide [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi, 4801192 (JP). USUI, Masanori [JP/JP]; c/o KABUSHIKI KAISHA TOYOTA CHUO KENKYUSHO, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi, 4801192 (JP).

- (74) Agent: TOKKYO GYOUMU HOUJIN KAIYU  
KOKUSAI TOKKYO JIMUSHO; NISSEKI MEITEKI  
BUILDING 7F, 45-14, Meieki 2-chome, Nakamura-ku,  
Nagoya-shi, Aichi, 4500002 (JP).

- (81) Designated States (unless otherwise indicated, for every country for which information is available): AE, AG, AL, AM,

*[Continued on next page]*

(54) Title: TRENCH GATE FIELD EFFECT DEVICES



(57) Abstract: The present invention relates to a technique for reducing the on-voltage of the semiconductor device by increasing the concentration of minority carriers in the deep region (26) and the intermediate region (28). A semiconductor device according to the invention comprises an electrode, a top region (36) of a second conductivity type connected to the electrode, a deep region of the second conductivity type, and an intermediate region of a first conductivity type connected to the electrode. A portion of the intermediate region isolates the top region and the deep region. The semiconductor device further comprises a gate electrode (32) facing the portion of the intermediate region via an insulating layer. The portion facing the gate electrode isolates the top region and the deep region. The semiconductor device according to the invention further comprises a barrier region (40) that is formed within the intermediate region and/or the top region.

**WO 2005/062385 A1**



AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.